



# FIXING BANDS

## TECHNICAL DATA SHEET AND BILL OF MATERIALS

PRODUCT CODE	PRODUCT NAME	TYPE	Length Meters	DIMENSIONS		HOLE SIZES		DISTANCE BETWEEN HOLES mm	PACKING TYPE	Ship Weight kg.	ROLLS/ CARTON pcs	BREAK LOAD kg *
				Width mm	Thickness mm	SMALL Ø mm	LARGE Ø mm					
FBR0312G	Fixing Band - Galvanised	Round, perforated	3 m	12	0.7		5	15	transparent clamshell	0.16	24	161
FBR1012G	Fixing Band - Galvanised	Round, perforated	10 m	12	0.7		5	15	blue plastic dispenser	0.48	10	161
FBR1017G	Fixing Band - Galvanised	Round, perforated	10 m	17	0.7		7	20	blue plastic dispenser	0.72	10	238
FBS0312G	Fixing Band - Galvanised	Straight, perforated	3 m	12	0.7		5	9	transparent clamshell	0.16	24	200
FBS1012G	Fixing Band - Galvanised	Straight, perforated	10 m	12	0.7	3.3	6.2	12	black plastic dispenser	0.48	10	143
FBS1019G	Fixing Band - Galvanised	Straight, perforated	10 m	19	0.7	3.3	8.3	18	black plastic dispenser	1.10	10	248
FBR1017SS	Fixing Band - Stainless Steel A2	Round, perforated	10 m	17	0.7		7	20	blue plastic dispenser	0.72	10	346

\* Values are actual break loads. A safety factor is necessary. The recommended factor - 3 to 6.

### MATERIALS USED

PERFORATED BAND	PLASTIC CASSETTE	PACKING
- Hot dip zinc coated steel (20µm) - DX51D+Z275 - A2 Stainless steel 1.4301 2B	HDPE	Corrugated fiberboard

