



Product Information

The Internal threaded Sockets provide a flush fixing which allows for the attachment of a suitable bolt or threaded rod.

Available in Zinc Plated, A2/304 and A4/316 Stainless Steel versions

Features

1. Expansion free
2. High Loads
3. Close Spacing and Edge Distance
4. Allows removal of bolt to leave a re-usable socket in place


Data is for Spin In Capsules and Vinyl Ester (Highload) Resin

Socket Data

Part Number			Thread Diam mm	Socket Length mm	Internal Thread Length mm	Drill Hole Diam mm	Hole Depth mm	Fixture Clearance Hole mm	Minimum Structure Thickness mm	Installation Torque Nm
Zinc Plated	Stainless Steel A2-304	Use With Capsule								
ITSM08BZP	ITSM08SS	JCAPSM12	8	90	30	14	90	10	110	7
ITSM10BZP	ITSM10SS	JCAPSM16	10	90	35	18	90	12	120	11
ITSM12BZP	ITSM12SS	JCAPSM16	12	90	40	25	90	14	140	25
ITSM016ZP	ITSM16SS	JCAPSM16	16	125	40	28	125	18	160	50

For A4/316 Stainless Steel version add A4 after Stainless Steel code

Installation Instructions



Drill correct diameter hole to correct depth

Clean hole by brushing and blowing to remove all dust and drilling debris

Insert Spin In Capsule with air bubble nearest to surface of concrete

Attach setting tool to socket and spin in with drilling machine using rotary hammer action flush with surfacel

Allow resin to cure, attach fixture, insert bolt and tighten to Recommended Torque

For injection resin inject resin to fill hole approx 1/3 full and insert socket rotating by hand to ensure even distribution of resin

For injection resin installation it is advisable to insert a bolt into the socket prior to installation to prevent resin entering the internal thread of the socket



Performance Data (C20/25 Concrete)									
Thread Diam mm	Characteristic Resistance kN		Design Resistance kN		Recommended Resistance kN		Spacing mm	Edge Distance mm	
	Tensile	Shear	Tensile	Shear	Tensile	Shear	Tensile & Shear	Tensile	Shear
8	25.6	9.0	12.2	7.2	8.7	5.7	135	80	90
10	35.5	14.0	16.9	11.2	12.1	8.5	180	90	125
12	43.5	21.0	20.7	16.8	14.8	11.3	200	100	160
16	76.9	39.0	36.6	31.2	26.1	14.2	250	125	270

Shear Resistance towards a free edge is for single anchors where Spacing $\geq 3 \times$ Edge Distance
 Loads are for Grade 5.8 Bolts and Grade 70 Stainless Steel Bolts

Reduced Design Resistance (kN) • Divide Resistance by 1.4 for Recommended Resistance

Edge Distance (C20/25 Concrete) for single anchors								
Edge mm	Tensile Resistance				Shear Resistance			
	M8	M10	M12	M16	M8	M10	M12	M16
45	8.5				3.6			
50	9.0	11.6			4.0			
55	9.5	12.3	14.2		4.4			
60	10.1	13.0	14.9		4.8			
65	10.6	13.6	15.6		5.2	5.8		
70	11.1	14.3	16.4	24.3	5.6	6.3		
80	12.2	15.6	17.8	25.3	6.4	7.2	8.4	
90		16.9	19.3	27.4	7.2	8.1	9.5	
100			20.7	29.4		9.0	10.5	
110				31.5		9.9	11.6	
120				33.5		10.8	12.6	
125				36.6		11.2	13.1	
140							14.7	16.2
160							16.8	18.5
180								20.8
200								23.1
220								25.4
250								28.9
270								31.2

Spacing (C20/25 Concrete)					
Spacing mm	Tensile Resistance per Pair of Anchors				
	M8	M10	M12	M16	
70	18.5				
80	19.4				
90	20.3				
100	21.2	26.3			
110	22.1	27.2			
120	23.0	28.2	33.1		
135	24.4	29.6	34.7		
150		31.0	36.2	58.6	
160		31.9	37.3	60.0	
170		32.9	38.3	61.5	
180		33.8	39.3	63.0	
190			40.4	64.4	
200			41.4	65.9	
210				67.3	
220				68.8	
230				70.3	
240				71.7	
250				73.2	

Influence of concrete strength

Concrete Strength		C20/25	C25/30	C30/37	C40/50	C50/60
Cylinder	N/mm ²	20	25	30	40	50
Cube	N/mm ²	25	30	37	50	60
Factor		1.00	1.10	1.22	1.41	1.55

When using concrete factors check all other information to ensure Steel Strength and Pull out Resistance is not exceeded

Steel Design Resistance for single anchor

		M8	M10	M12	M16	
Tension	kN	12.0	19.3	28.0	52.0	Grade 5.8 Bolts
	kN	13.9	21.4	31.5	58.8	Stainless Steel Grade 70
Shear	kN	7.2	11.2	16.8	31.2	Grade 5.8 Bolts
	kN	8.3	12.8	18.5	35.2	Stainless Steel Grade 70

Anchor mechanical properties

		M8	M10	M12	M16	
Nominal Tensile Strength	N/mm ²	500	500	500	500	Zinc plated
		700	700	700	700	Stainless Steel
Yield Strength	N/mm ²	400	400	400	400	Zinc plated
		450	450	450	450	Stainless Steel